
.50

OWNER'S GUIDE



ASSEMBLY
OPERATION
MAINTENANCE
PARTS LIST

IMPORTANT: Read Safety Rules and Instructions MODEL NUMBERS 110-112A 110-122A

> 20" & 22" ROTARY MOWERS

INDEX

Safa Operation Practices 3	Using Your Rotary Mower9
Accomply Instructions 4	Off-Season Storage9
Operation Instructions6	
Adjustments6	Repair Parts List13
Lubrication	
Maintenance 8	

LIMITED WARRANTY

For one year from the date of original retail purchase, MTD PRODUCTS INC will either repair or replace, at its option, free of charge, F.O.B. factory or authorized service firm, any part or parts found to be defective in material or workmanship. Transportation charges under this warranty must be paid by the purchaser unless return is requested by MTD PRODUCTS INC.

This warranty will not apply to any part which has become inoperative due to misuse, excessive use, accident, neglect, improper maintenance, alterations, or unless the unit has been operated and maintained in accordance with the instructions furnished. This warranty does not apply to the engine, motor, battery, battery charger or component parts thereof. Please refer to the applicable manufacturer's warranty on these items.

This warranty will not apply where the unit has been used commercially.

Warranty service is available through your local authorized service dealer or distributor. If you do not know the dealer or distributor in your area, please write to the Customer Service Department of MTD.

The return of a complete unit will not be accepted by the factory unless prior written permission has been extended by MTD.

This warranty gives you specific legal rights. You may also have other rights which vary from state to state.

WARNING TO PURCHASERS OF INTERNAL COMBUSTION ENGINE EQUIPPED MACHINERY OR DEVICES IN THE STATE OF CALIFORNIA

The equipment which you have just purchased does not have a spark arrester. If this equipment is used on any forest covered land, brush covered land, or grass covered unimproved land in the State of California, before using on such land, the California law requires that a spark arrester be provided. In addition, spark arrester is required by law to be in effective working order. The spark arrester must be attached to the exhaust system and comply with Section 4442 of the California Public Resources Code.



It is suggested that this manual be read in its entirety before attempting to assemble or operate. Keep this manual in a safe place for future reference and for ordering replacement parts.

This unit is shipped WITHOUT GASOLINE or OIL. After assembly, see operating section of this manual for proper fuel and amount.

Your rotary mower is a precision piece of power equipment, not a plaything. Therefore exercise extreme caution at all times.

SAFE OPERATION PRACTICES FOR WALK-BEHIND MOWERS

TRAINING

- Read the Operating and Service Owner's Manual carefully. Be thoroughly familiar with the controls and the proper use of the equipment.
- Never allow children to operate a power mower. Only persons well acquainted with these rules of safe operation should be allowed to use your mower.
- 3. Keep the area of operation clear of all persons, particularly small children and pets. Stop engine when they are in the vicinity of your mower. Although the area of operation should be completely cleared of foreign objects, a small object may have been overlooked and could be accidently thrown by the mower in any direction.

PREPARATION

- Thoroughly inspect the area where the equipment is to be used and remove all stones, sticks, wire, bones and other foreign objects which could be picked up and thrown by the mower in any direction.
- Do not operate equipment when barefoot or wearing open sandals. Always wear substantial footwear.
- Do not wear loose fitting clothing that could get caught on the mower.
- 4. Check the fuel before starting the engine. Do not fill the gasoline tank indoors, when the engine is running, or while the engine is still hot. Wipe off any spilled gasoline before starting the engine.
- Disengage the self-propelled mechanism or drive clutch on units so equipped before starting the engine.
- Never attempt to make a wheel or cutting height adjustment while the engine is running.
- 7. Mow only in daylight or in good artificial light.
- 8. Never operate the equipment in wet grass. Always be sure of your footing; keep a firm hold on the handle and walk, never run.

OPERATION

- Do not change the engine governor settings or overspeed the engine. Excessive engine speeds are dangereous.
- Do not put hands or feet near or under rotating parts. Keep clear of the discharge opening at all times.
- Stop the blade(s) when crossing gravel drive, walks or roads.
- 4. After striking a foreign object, stop the engine, remove the wire from the spark plug,

- thoroughly inspect the mower for any damage, and repair the damage before restarting and operating the mower.
- If the equipment should start to vibrate abnormally, stop the engine and check immediately for the cause. Vibration is generally a warning of trouble.
- Stop the engine whenever you leave the mower, before cleaning the mower housing, and when making any repairs or inspections.
- 7. When cleaning, repairing or inspecting, make certain the blade and all moving parts have stopped. Disconnect the spark plug wire, and keep the wire away from the plug to prevent accidental starting.
- Before attempting to unclog the mower or discharge chute, stop the engine and be sure the blade(s) have stopped completely. Disconnect the spark plug wire and keep the wire away from the plug to prevent accidental starting.
- 9. Do not run the engine indoors.
- Shut the engine off and wait until the blade comes to a complete stop before removing the grass catcher or unclogging chute.
- 11. Mow across the face of slopes, never up-anddown. Exercise extreme caution when changing direction on slopes. Do not mow excessively steep slopes.
- Always disconnect electric mowers (line operated) before cleaning, repairing or adjusting.
- Never operate mower without proper guards, plates or other safety protective devices in place.
- 14. Keep washout ports and other mower-housing service openings closed when mowing.

MAINTENANCE AND STORAGE

- 1. Check the blade and engine mounting bolts at frequent intervals for proper tightness.
- Keep all nuts, bolts, and screws tight to be sure the equipment is in safe working condition.
- Never store the equipment with gasoline in the tank inside of a building where fumes may reach an open flame or spark. Allow the engine to cool before storing in any enclosure.
- 4. To reduce fire hazard, keep the engine free of grass, leaves, or excessive grease.
- Check the grass catcher bag frequently for wear or deterioration. For safety protection replace only with new bag meeting original equipment specifications.




FIGURE 1.




FIGURE 2.




FIGURE 3.

ASSEMBLY INSTRUCTIONS

- Extend throttle control which is attached to the engine at the rear of the mower and place on the floor. Be careful not to bend or kink control wire.
- Fasten lower handle in position over weld pins in handle mount brackets on deck.
 Secure with hairpin cotters in inner hole on weld pin. See figure 1.



There are two (2) holes in the handle mount brackets. Place the lower handle against the brackets and secure with hairpin cotter in the inner hole. Inner hole is for operation. Outer hole is for storage.



It may be necessary to pull open the ends of the lower handle. This will insure a tight fit when assembled into handle mount brackets.

3. Assemble upper handle to lower handle.

Secure with two carriage bolts and hex lock nuts as shown in figure 2.



There are two height positions for the handle. See adjustment section.

4. Place the throttle control in position on right side of upper handle. Secure with hex bolt and lock nut. See figure 3.



Reference to right and left hand sides of the unit is observed from the operating position.




FIGURE 4.




FIGURE 5.

- 5. Secure throttle control cable to handle with ties provided. See figure 4.
- 6. Check ALL nuts and bolts for correct tightness.



Please note that the chute deflector on your mower is in an upright position. It is held in that position by a shipping block. This block is used for shipping purposes only. It must be removed and discarded before your mower is put into operation. See figure 5.

OPERATION





FIGURE 6.

Keep hands and feet away from the chute area on cutting deck. See figure 6.



For shipping purposes your mower is set with the wheels in a low cutting height position. For best results raise the cutting position until it is determined which height is best for your lawn. See adjustment section.

 FILL SUMP WITH OIL—Use a high quality detergent oil classified "For Service SC, SD, SE or MS". Nothing should be added to the recommended oil.

SUMMER
(Above 40° F.)
Use SAE 30
If not available,
Use SAE 10W-30
or

SAE 10W-40

WINTER
(Under 40° F.)
Use SAE 5W-20 or SAE 5W-30
If not available,
Use SAE 10W or SAE 10W-30

DIRECTIONS: Place the engine level. Remove oil filler plug. FILL THE OIL SUMP TO POINT OF OVERFLOW. Pour slowly. Capacity 11/4 pints.

- FILL FUEL TANK—Use clean, fresh, lead-free or leaded "regular" grade automotive gasoline. Fill tank completely!
 DO NOT MIX OIL WITH GASOLINE.
- 3. When ready to start engine, place throttle control lever on handle in "START" position and start engine in accordance with instructions in engine manual. After engine starts, move throttle control lever on handle to desired engine speed. The engine is stopped by placing control lever on handle in the "STOP" position.
- 4. Be sure that lawn is clear of stones, sticks, wire, or other objects which could damage lawn mower or engine. For best results and to insure more even grass distribution, do not mow when lawn is excessively wet.



After striking a foreign object, stop the engine. Remove wire from spark plug, thoroughly inspect the mower for any damage, and repair the damage before restarting and operating the mower.

ADJUSTMENTS



Do not at any time make any adjustment to lawn mower without first stopping engine and disconnecting spark plug wire.

EASY CUTTING HEIGHT

An adjusting plate and thumb lever at each wheel position provides cutting height adjustment. Each adjusting plate has five holes. Height of cut will be changed when the thumb lever is moved from one hole to another. Simply depress thumb lever towards wheel and move wheel and lever assembly to desired position. All wheels must be positioned in relative height of cut positions.

HANDLE POSITION

The upper handle can be adjusted to a high or low position. the adjustment is made by removing the hex lock nuts and curved carriage bolts and reassembling in the other position. A ½" wrench is required. See figure 7.




FIGURE 7. THROTTLE

If adjustment becomes necessary, the throttle control wire assembly can be reset as follows:

- Loosen, but do not remove, screw securing throttle control wire assembly at engine. See figure 8.
- 2. Move throttle control lever on handle to "FAST" position.
- 3. Move lever, to which control wire is fastened at engine, to full open position and retighten screw to secure throttle control wire assembly.




FIGURE 8.



If any adjustments are made to the engine while the engine is running (e.g. carburetor), disengage all clutches and blades. Keep clear of all moving parts and be careful of heated surfaces and muffler.

CARBURETOR ADJUSTMENTS (See figure 9.)

Minor carburetor adjustment may be required to compensate for differences in fuel, temperature, altitude and load.

All carburetor adjustments should be made with the air cleaner on engine. Air cleaner mounting screw must be in carburetor when engine is run. Best adjustment is made with a fuel tank half full of gasoline.

To Adjust Carburetor:

- Start engine and run long enough to warm it to operating temperature. If engine is out of adjustment so that it will not start, close the needle valve by turning it clockwise. Then open needle valve 1½ turns counterclockwise.
- Move engine control to run engine at normal operating speed.
 - a. Turn needle valve in clockwise until engine starts to lose speed (lean mixture).
 - b. Then slowly turn needle valve out counterclockwise past the point of smoothest operation until engine just begins to run unevenly (rich mixture).
 - c. Turn needle valve back in clockwise very slowly till engine runs evenly.
 - d. Final adjustment of the needle valve should be slightly to the rich side (turn counterclockwise) of the mid-point.
- 3. Move engine control to "SLOW". Turn idle adjusting screw until a fast idle is obtained—(1750 R.P.M.).
- 4. To check adjustment move engine control from "SLOW" to "FAST" speed. Engine should accelerate smoothly. If engine tends to stall or die out, increase idle speed or readjust carburetor, usually to a slightly richer mixture.




FIGURE 9.

LUBRICATION



Always stop engine and disconnect spark plug wire before cleaning, lubricating or doing any kind of work on lawn mower.

Wheels—Wheel bearings are of self-lubricating Fortiflex. They require no lubrication. If your unit is provided with optional ball bearing wheels, lubricate at least once a season with light oil.

Protective Shield—The pivot points on the protective shield should be lubricated periodically with light oil to prevent any rust or binding.

Chute Deflector—The torsion spring and pivot point should be lubricated periodically with light oil to prevent any rust or binding. Deflector must work freely.

Engine—Follow engine manual for lubrication instructions.

Throttle—Periodically lubricate throttle control lever and throttle wire assembly with a few drops of light oil (SAE No. 10 or 20) for ease of operation.

MAINTENANCE

CUTTING BLADE

The blade may easily be removed for grinding or replacement as follows:

- 1. Remove bolt and lockwasher holding blade and blade adapter to engine crankshaft.
- 2. Remove blade and blade adapter from engine crankshaft.
- 3. Remove two bolts, lockwashers and nuts holding blade to blade adapter (if necessary).

When sharpening blade, follow the original angle of grind as a guide. It is extremely important that each cutting edge receives an equal amount of grinding to prevent an unbalanced blade. An unbalanced blade will cause excessive vibration when rotating at high speeds and may cause damage to the mower.

To insure safe operation of your unit, ALL nuts and bolts must be checked periodically for correct tightness.

DECK

The underside of mower deck should be cleaned after each period of use as grass clippings, leaves, dirt and other matter will accumulate. This accumulation of grass clippings, etc., is undesirable as it will invite rust and corrosion and may cause an uneven discharge of grass clippings at the next cutting.

The deck may be cleaned by tilting the mower forward or on its side and scraping clean with a suitable tool or by washing with a stream of water from a garden hose.



Do not direct the stream of water at a hot engine as damage to the engine may result.

ENGINE OIL

CHECK OIL LEVEL before starting engine and after every 5 hours of operation.

ADD oil as necessary to keep level FULL TO POINT OF OVERFLOWING.

Before removing oil fill plug, clean area around plug to prevent dirt from entering oil fill hole.

Engine should be in a level position when checking oil.

CHANGE OIL after first 5 hours of operation. Thereafter change every 25 hours. Change oil while engine is warm. Oil may be drained thru drain on bottom of engine. To drain completely, always place engine level when draining thru the bottom. Oil capacity 1-1/4 pints. See figure 10.



FIGURE 10.

AIR CLEANER

CLEAN AIR CLEANER and re-oil element every 25 hours under normal conditions. Clean every few hours under extremely dusty conditions. Poor engine performance and flooding usually indicates that the air cleaner should be serviced. See figure 11.

- 1. Remove screw.
- 2. Remove air cleaner carefully to prevent dirt from entering carburetor.
- 3. Take air cleaner apart and clean.
 - a. WASH foam element in kerosene or a liquid detergent and water to remove dirt.
 - b. DRY foam completely by wrapping and squeezing in a cloth.
 - c. SOAK foam with engine oil. Squeeze to distribute and remove excess oil.
- 4. Reassemble parts and fasten to carburetor.




FIGURE 11.




FIGURE 12.




FIGURE 13.

SPARK PLUG

The spark plug gap should be cleaned (see figure 12) and reset to a 0.030-inch clearance once a season (see figure 13). Spark plug replacement is recommended at the start of each mowing season; check engine parts list for correct plug type.



Whenever the spark plug is removed for cleaning, it is advisable to replace the spark plug gasket with a new gasket.

USING YOUR ROTARY MOWER

For the best results do not cut wet grass because it tends to stick to the underside of the mower, thus preventing proper discharge of grass clipings. If wet grass must be cut, reduce walking speed to help distribute the clippings more effectively.

New grass should be treated as wet grass, otherwise a normal walking speed is about the right pace for efficient mowing.

The best mowing pattern is one that allows the clippings to discharge towards the uncut part of the lawn. This permits recutting of the clippings to further pulverize them. When cutting high weeds, discharge towards cut portion, then recut at right angles to first direction.

Lawn should be cut in the fall as long as there is growth.

OFF-SEASON STORAGE

The following steps should be taken to prepare lawn mower for storage.

- 1. Clean and lubricate mower thoroughly as described in the lubrication instructions.
- 2. Refer to Engine Manual for correct engine storage instructions.
- 3. Coat mower's cutting blade with chassis grease to prevent rusting.
- 4. Place blocks under deck to raise tires clear of floor.
- 5. Store mower in a dry, clean area.

HANDLE STORAGE

The handle may be placed in an upright position for storage.

Move the hairpin cotters to the outer hole on weld pins. See figure 1. Press inward on the bottom of the lower handle and push forward. The handle will lock in this position.

Reverse the above procedure to place the handle in the operating position.



The manufacturer DOES NOT recommend the use of any accessory on this Rotary Mower other than those manufactured by the mower manufacturer.

GRASS CATCHER Model No. 190-003A is available as optional equipment for the mowers shown in this manual.



- 1. The mower should not be operated without the entire grass catcher or chute deflector in place.
- 2. The mower should not be operated without the protective shield on the rear of the deck in place.



Under normal usage bag material is subject to wear and should be checked periodically. Be sure any replacement bag complies with the mower manufacturer's recommendations.

For replacement bags, use only factory authorized replacement bag No. 764-0176.

110-112A IF YOU WRITE TO US ABOUT THIS ARTICLE OR IF YOU ORDER REPLACEMENT PARTS AL-WAYS MENTION THIS MODEL & SERIAL NO MODEL 110-122A 52 10 36 13 17 16 <u>3</u>3 *3*5 -20 -21 24-23 -22 *33* 32

PARTS LIST FOR MODELS 110-112A AND 110-122A

7	REF. NO.	PART NO.	COLOR CODE	DESCRIPTION	NEW PART	REF. NO.	PART NO.	COLOR CODE	DESCRIPTION	NEW PART
	1 2 3 4	718-0145 749-0384 712-0158 710-0671	1 3	Grip Upper Handle Hex Cent. L-Nut 5/16-18 Thd. Curved Hd. Carr. Bolt 5/16-18 x 1.38	N	28 29 30	10937 736-01 736-02 712-01	19	Pivot Bar Bell. Wash. 3/8" I.D. Bell. Wash400 I.D. x 1.130 O.D. Elastic Stopnut	
	5 6 7	749-0373 12945 710-0567		Lower Handle Handle Mount Brkt.—L.H. Hex Bolt ¼-28 x .62" Lg. Nylock	N	32	734-08 734-06	76	Wheel Ass'y. Comp. (110-112A) Wheel Ass'y. Comp. (110-122A)	
	8 10	3 H.P. 3½ H.P. 10941		Engine (110-112A) Engine (110-122A) Height Adjuster Ass'y. Comp.—L.H.		33 34 35	741-02 738-01 11679	02	Fortiflex Brg. (2 per wheel) Axle Bolt Chute Deflector Ass'y. Comp.	
	12 13	710-0654 11410		Hex Wash. Hd. Self-Tap Scr. 3/8-16 x 1.25" Lg. 20" Deck Ass'y. (110-112A)	N	36 37 38	10949 710-02 11130		Spring Lever Ass'y. w/Knob Hex Bolt 1/4-20 x .50" Lg.* Adapter Plate	
	14 15	11412 711-0555 712-0107 10934 10938	—462 5	22" Deck Ass'y. (110-122A) Pivot Pin Hex Cent. L-Nut ¼-20 Thd. Index Plate Ass'y.—R.H. Height Adjuster Ass'y.		39 41 42 43	726-01 710-06 732-02 10937	06 00 53	Push-On Flange Palnut Hex Wash. Hd. Self Tap Scr. 5/16-24 x .50" Lg. Torsion Spring Index Plate Ass'y.—L.H.	
	18	714-0365	5	Comp.—R.H. #6 Hi-Pro Key 5/32 x 5/8" Dia.		45 46 47	12946 714-01 726-01	04 88	Handle Mount Brkt.—R.H. Hairpin Cotter Cable Tie—7/8"	
	19 20 21 22	10769 742-0125 742-0125 736-0217 710-0459	5 7	Blade Adapter Kit 20" Blade (110-112A) 22" Blade (110-122A) L-Wash. 3/8" Scr.—H.D. Hex Bolt 3/8-24 x 1.50" Lg.—		48 49 50 51	11193 14084 726-01 746-02 746-02	—462 34 29	Rear Shield Ass'y. (110-112A Rear Shield Ass'y. (110-122A Speed Nut #8-32—Twin Type Conduit and Wire Throttle Control Ass'y.) N
	23 24	10769 710-0117		H.T. Blade Adapter Kit Hex Bolt 5/16-24 x 1.00"		52	731-03	44	Comp. Plastic Throttle Control Cover	
	25 26 27	736-0119 712-0123 710-0209	3	Lg.—H.T. L-Wash. 5/16" Scr.* Hex Nut 5/16-24 Thd.* Hex Sems Bolt 3/8-16 x .62" Lg.*		53 54	710-06 712-01		Hex Bolt ¼-20 x 1.50" Lg.* Hex Cent. L-Nut ¼-20 Thd.	

(462-Red Flake)

When ordering parts, if color or finish is important use the appropriate color code shown above (e.g. Red Flake Finish—11409 (462).)

The engine is not under warranty by the mower manufacturer. If repairs or service is needed on the engine, please contact your nearest authorized engine service outlet. Check the "Yellow Pages" of your telephone book under "Engines — Gasoline."





This instruction manual covers various models and all specifications shown do not necessarily apply to your model. Specifications subject to change without notice or obligation.

^{*}For faster service obtain standard nuts, bolts and washers locally. If these items cannot be obtained locally, order by part number and size as shown on parts list.

PARTS INFORMATION

POWER EQUIPMENT PARTS AND SERVICE

Parts and service for all MTD manufactured power equipment are available through the authorized service firms listed below. All orders should specify the model number of your unit, parts number, description of parts and the quantity of each part required.

ALABAMA Auto Electric & Carburetor Co	BIRMINGHAM 2625 4th Ave. S 35233
ARKANSAS	FORT SMITH
	4515 South 16th Street 72901
	NORTH LITTLE ROCK
Sutton's Lawn Mower Shop	Rt. 4 Box 36872117
CALIFORNIA	PORTERVILLE 75 North D Street 93257
Billious	75 North D Street 93257
Lawn Mower Supply Co	SAN BERNARDINO 25608 E. Baseline 92410
Lawii Wowei Supply Co	SAN FRANCISCO
J.W. Jewett Co	SAN FRANCISCO . 981 Folsom St 94107
COLORADO	DENVER 527 West Evans 80223
South Denver Lawn Equip	527 West Evans 80223
FLORIDA	JACKSONVILLE
Radco Distributors	2403 Market St 32206
Small Eng Diet	OPA LOCKA 2351 N.W. 147th St 33054
GEORGIA	FAST POINT
Fast Point Cycle & Key	EAST POINT 2834 Church St 30344
ILLINOIS	LYONS
Keen Edge Co	LYONS 8615 Ogden Ave 60534
INDIANA	ELKHART 2101 Industrial Pkwy 46514
Parts & Sales Inc	2101 Industrial Pkwy 46514
IOWA	DUBUQUE 2551 J.F. Kennedy 52001
LOUISIANA	NEW ORLEANS
Suhren Engine Co	NEW ORLEANS8330 Earhart Blvd70118
MARYLAND	TAKOMA PARK
Center Supply Co	TAKOMA PARK 6867 New Hampshire Ave 20012
MASSACHUSETTS Morton B. Collins Co	SPRINGFIELD
	LANCING
Lavana Camilaa Ca	2500 C Bannoulyania 49010
Loronz Gorrioc Go	MOUNT CLEMENS
Power Equipment Dist	MOUNT CLEMENS 36463 South Gratiot 48043 HOPKINS 420 Excelsior Ave. W 55343
MINNESOTA	HOPKINS
Hance Distributing Inc	420 Excelsior Ave. W 55343
Dower Tools Inc. 2	ST. PAUL 771 Sibley Memorial Hwy 55122
MISSISSIPPI	RII OXI
Biloxi Sales & Service, Inc	BILOXI 506 Caillavet St 39533
MISSOURI	KANSAS CITY 3117 Holmes St 64109
Automotive Equip. Service	3117 Holmes St 64109
	ST. JOSEPH8th and Monteray64503
Ross-Frazier Supply Co	ST. LOUIS
Honzler Inc	ST. LOUIS 2015 Lemay Ferry Rd 63125
NEW JERSEY	BELLMAWR
Lawnmower Parts Inc	717 Creek Rd 08030
	RUTHERFORD
Feld Distributor	28 Glen Rd07070
NEW YORK	CARTHAGE West End Ave 13619
Gamble Dist., Inc.	west End Ave 13619

BRIGGS AND STRATTON, TECUMSEH AND PEERLESS PARTS AND SERVICE

Briggs & Stratton, Tecumseh and Peerless parts and service should be handled by your nearest authorized engine service firm. Check the yellow pages of your telephone directory under the listing Engines—Gasaline, Briggs & Stratton or Tecumseh Lauson.

Engines—Gasaline, Briggs & Stratto	
CTD Laisura Droducto Inc	SYRACUSE 420 Marcellus St 13204
MODIL CAROLINA	COLDSBORO
NORTH CAROLINA Smith Hardware Co	E15 N Coorde Ch 07500
Smith Hardware Co	515 N. George St 27530
Divis Salas Company	GREENSBORO 327 Battleground Ave. 27402
OHIO	CARROLL
Stebe's Mid-State Mower Supply	Box 366-71 High St 43112
	CLEVELAND
Bleckrie, Inc	7900 Lorain Ave 44102
	WADSWORTH
National Central	687 Seville Rd 44281
	YOUNGSTOWN
Burton Supply Co	301 Logan Ave. Box 929 44501
OKLAHOMA	ADA 301 E. 12th St 74820
Ada Auto Supply	301 E. 12th St 74820
Victory Motors, Inc	MUSKOGEE
Victory Motors, Inc	605 S. Cherokee /4401
	OKLAHOMA CITY
Forest Sales Inc	1039 NW 63rd St 73116 PORTLAND
OREGON Kenton Supply Co	PORTLAND
PENNSYLVANIA	CHESTER
PENNSTLVANIA	742 W. Front St 19013
Stull Equipment Corp	HARRISBURG
EECO Inc	4021 N. 6th St 17110
EECO IIIC	4021 N. 0(11 St 17 110
Ti annua an Dahban Oa	PHILADELPHIA 5222-24 N. Fifth St 19120
	PITTSBURGH
Divisionant Co	11125 Frankstown Rd. 15235
TENNECCEE	KNOVULLE
Moster Depoir Convice	2000 Western Ave 37921
Master Repair Service	MEMPHIS
	421 Monroe Ave 3810
American Sales & Service Inc	1922 Lynnbrook 38116
TEXAS	DALLAS
Marr Brothers Inc	423 E. Jefferson 75203
Man Brothers, mo	FORT WORTH
Woodson Sales Corn	1702 N. Sylvania 76111
Woodson cales corp	HOUSTON
Builard Supply Co.	2409 Commerce St 77003
	SAN ANTONIO
Catto & Putty, Inc	414 Live Oak 78298
UTAH	SALT LAKE CITY
A-1 Engine & Mower Co	SALT LAKE CITY 437 E. 9th St 84111
VERMONT	BURLINGTON
Vermont Hdwe. Co. Inc	180 Flynn Ave 05401
VIRGINIA	RICHMOND
RBI Corp	963 Myers St 23260
WASHINGTON	SEATTLE
Bailey's Inc	1414 14th Ave 98102
WEST VIRGINIA	CHARLESTON
Young's, Inc	CHARLESTON 233 Virginia St., E 25301
WISCONSIN	APPLETON 123 S. Linwood Ave 54911
Automotive Supply Co	123 S. Linwood Ave 54911

WARRANTY PARTS AND SERVICE POLICY

The purpose of warranty is to protect the customer from defects in workmanship and materials, defects which are NOT detected at the time of manufacture. It does not provide for the unlimited and unrestricted replacement of parts. Use and maintenance are the responsibility of the customer. The manufacturer cannot assume responsibility for conditions which it has no control. Simply put, if it's the manufacturer's fault, it's the manufacturer's responsibility; if it's the customer's fault, it's the customer's responsibility.

CLAIMS AGAINST THE MANUFACTURER'S WARRANTY INCLUDES

- 1. Replacement of Missing Parts on new equipment.
- 2. Replacement of Defective Parts within the warranty period.
- 3. Repair of Defects within the warranty period.

All claims MUST be substantiated with the following information:

- 1. Madel Number of unit involved.
- 2. Date unit was purchased or first put into service.
- 3. Date of failure.
- 4. Nature of failure.